



 **ascendo**

***THE LEGEND RISES
BE BOLD BE STRONG***





PT. ASCENDO INTERNASIONAL



PT. ASCENDO INTERNASIONAL is a professional company that committed to produce the best quality tires and tubes for motorcycles, trucks and forklift producer in the world, reputable for its high-quality products, supported by the best production technologies, and managed by thorough international standard quality control systems. With our SNI, ISO 9001:2015, Europe Chemical Compliance (REACH) and others. Our products are successfully exported to Europe, US, and all around the globe.

With our long history, experiences, and knowledge of Solid Tires, we proudly introduce our new solid tires variety. We believe that our complete range of tires and tubes will satisfy your business needs.





51000 52000

51000				O.D.	S.W.	Weight	Load Capacity (kg)				
							Forklift		Others		
Size	Type	LIP	STD. Rim	mm	mm	kg	Load	Steer	Up to 6km/h	Up to 10km/h	Up to 25km/h
6.00-9	Solid	✓	4.00E	524	148	28.6	2340	1885	1885	1710	1450
6.50-10	Solid	✓	5.00F	576	161	38.0	2340	1800	2340	2125	1800
7.00-12	Solid	✓	5.00S	658	179	51.7	2920	2240	2920	2645	2240

52000				O.D.	S.W.	Weight	Load Capacity (kg)				
							Forklift		Others		
Size	Type	LIP	STD. Rim	mm	mm	kg	Load	Steer	Up to 6km/h	Up to 10km/h	Up to 25km/h
15x4-1/2-8	Solid	✓	3.00D	380	109	9.70	1040	800	1040	945	800
16x6-8	Solid	✓	4.33R	414	141	16.3	1495	1150	1495	1360	1150
5.00-8	Solid	✓	3.00D	453	115	16.4	1415	1090	1415	1285	1090
18x7-8	Solid	✓	4.33R	451	148	20.6	2145	1650	2145	1945	1650
140/55-9	Solid	✓	4.00E	382	130	11.0	1170	900	1170	1060	900
6.00-9	Solid	✓	4.00E	528	141	27.6	1885	1450	1885	1710	1450
21x8-9	Solid	✓	6.00E	523	186	35.0	2755	2120	2755	2500	2120
200/50-10	Solid	✓	6.50F	461	195	25.0	2470	1900	2470	2240	1900
6.50-10	Solid	✓	5.00F	574	157	36.5	2340	1800	2340	2125	1800
23x9-10	Solid	✓	6.50E	587	199	48.5	3445	2650	3445	3125	2650
7.00-12	Solid	✓	5.00S	567	170	48.9	2920	2240	2920	2645	2240
23x10-12	Solid	✓	8.00G	592	237	52.6	3770	2900	3770	3420	2900
27x10-12	Solid	✓	8.00G	677	237	75.5	3900	3000	3900	3540	3000
6.00-15	Solid		4.50E	697	151	43.0	2455	1820	2455	2095	1820
7.00-15	Solid		5.50	739	170	57.3	3545	2725	3545	3215	2725
7.50-15	Solid		6.00	765	194	74.2	3900	3000	3900	3540	3000
	Solid		6.50	765	194	74.5	3900	3000	3900	3540	3000
28x9-15	Solid	✓	7.00	692	208	59.2	3900	3000	3900	3540	3000
2.50-15 (250/70-15)	Solid	✓	7.00	711	222	69.0	4745	3650	4745	4310	3650
	Solid	✓	7.50	711	222	69.4	4745	3650	4745	4310	3650
8.25-15	Solid	✓	6.50	813	198	91.0	4750	3650	4750	4300	3650
3.00-15 (315/70-15)	Solid	✓	8.00	811	255	109.0	5850	4500	5850	5310	4500
7.50-16	Solid		6.00	789	185	76.6	3950	3600	3050	3050	4605
9.00-20	Solid		7.00	1,013	229	151.0	5400	4500	5400	4905	4500
	Solid		7.50	1,013	230	151.5	5400	4500	5400	4905	4500
10.00-20	Solid		7.50	1,030	250	170.7	6000	5000	6000	5450	5000
	Solid		8.00	1,030	251	171.2	6000	5000	6000	5450	5000
12.00-20	Solid		8.00	1,100	279	226.4	7560	6300	7560	6865	6300
	Solid		8.50	1,100	279	226.7	7560	6300	7560	6865	6300



S3000 S200R

S3000				O.D.	S.W.	Weight	Load Capacity (kg)				
Size	Type	LIP	STD. Rim				Forklift		Others		
				mm	mm	kg	Load	Steer	Up to 6km/h	Up to 10km/h	Up to 25km/h
15x4.5-8	Solid	✓	3.00D	383	110	9.80	1040	800	1040	945	800
16x6-8	Solid	✓	4.33R	414	144	15.8	1495	1150	1495	1360	1150
5.00-8	Solid	✓	3.00D	453	120	15.9	1415	1090	1415	1285	1090
18x7-8	Solid	✓	4.33R	452	153	20.5	2145	1650	2145	1945	1650
6.00-9	Solid	✓	4.00E	528	145	27.1	1885	1450	1885	1710	1450
21x8-9	Solid	✓	6.00E	523	181	35.0	2755	2120	2755	2500	2120
200/50-10	Solid	✓	6.50F	461	195	25.0	2470	1900	2470	2240	1900
6.50-10	Solid	✓	5.00F	574	162	36.0	2340	1800	2340	2125	1800
23x9-10	Solid	✓	6.50E	587	199	48.0	3445	2650	3445	3125	2650
7.00-12	Solid	✓	5.00S	567	170	48.8	2920	2240	2920	2645	2240
23x10-12	Solid	✓	8.00G	592	237	52.5	3770	2900	3770	3420	2900
6.00-15	Solid		4.50E	697	151	43.0	2455	1820	2455	2095	1820
7.00-15	Solid		5.50	739	170	57.3	3545	2725	3545	3215	2725
28x9-15	Solid	✓	7.00	693	208	59.2	3445	2650	3445	3125	2650
8.25-15	Solid	✓	6.50	813	198	91.0	4750	3650	4750	4300	3650
300-15 (315/70-15)	Solid	✓	8.00	812	255	109.5	5850	4500	5850	5310	4500
11.00-20	Solid		7.50/8.00	1,076	282	211.3	6540	5450	6540	5940	5450

S200R & Smooth				O.D.	S.W.	Weight	Load Capacity (kg)				
Size	Type	LIP	STD. Rim				Forklift		Others		
				mm	mm	kg	Load	Steer	Up to 6km/h	Up to 10km/h	Up to 25km/h
4.00-8	Solid	RIB	3.00D	404	108	11.3	950	730	950	860	730
10.00-20	Solid		7.50	1,016	225	155.0	6000	5000	6000	5450	5000

3 Layer Design

TREAD LAYER

Designed to endure wear and abrasions while at the same time provides high durability and tear resistance during work.

CENTER LAYER

Natural rubber compound provides low heat buildup, rolling resistance, deflection without reducing its softness and pliancy

BASE LAYER

Combined with steel reinforced rings for stability and perfect grip.



Special Features of Ascendo Solid Resilient Tires :



Cut Resistance

Reduces chunking and cutting on rough and jagged surfaces



Cushion

Shock absorbance and enhanced driver comfort



Heat Resistance

Continuous operation ensured by low built-up structure compound



Mileage

Wide tread and maximum volume of the wear-resistant compound for extra mileage.



PT. ASCENDO INTERNASIONAL

Jl. Palmerah Barat No. 8
Kel. Grogol Utara Kec. Kebayoran Lama
Jakarta Selatan 12210
INDONESIA
Tel : +62 21 530 6869 / 530 8151
Fax : +62 21 530 8189

PT. ARAMI JAYA

Jl. Deandels Rt. 02 Rw. 03
Harjo Binangun Kec. Grabag
Purworejo, Yogyakarta
INDONESIA